



SAFETY DATA SHEET

PRO-SPRAY H20 BASECOAT SPOT REPAIR FAST THINNER

Page 1

Issued: 04/08/2010

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name: PRO-SPRAY H20 BASECOAT SPOT REPAIR FAST THINNER

Product code: HTH-300

PR Number: 2083437

Company name: Pro-Spray Automotive Finishes Limited

Unit H

Normandy Lane, Stratton Business Park

Biggleswade

Bedfordshire

SG18 8QB

United Kingdom

Tel: +44 (0) 1767 314320

Fax: +44 (0) 1767 319044

Emergency tel: +44 (0) 1767 314320 (office hours only)

Email: colour@pro-spray.co.uk

2. HAZARDS IDENTIFICATION

Classification under CHIP: Irritating to eyes. Vapours may cause drowsiness and dizziness.

Workplace exposure limit: This product does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This mixture meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: PROPAN-2-OL 10-30%

EINECS: 200-661-7 CAS: 67-63-0

[F] R11; [Xi] R36; [-] R67

CLP Class: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336

4. FIRST AID MEASURES

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. If outside keep bystanders upwind and away from danger point.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: PROPAN-2-OL
UK - 8 hour TWA: 999 mg/m³
UK - 15 min. STEL: 1250 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: Compressed airline breathing apparatus (EN139). Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Odour: Characteristic odour

Solubility in water: Not miscible

Flash point°C: 14

VOC g/l: 788

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to eyes.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1263

ADR Class: 3

Packing group: II

Classification code: F1

Shipping name: PAINT RELATED MATERIAL

Labelling: 3

Hazard ID no: 33

IMDG / IMO

UN no: 1263

Class: 3

Packing group: II

EmS: F-E,S-E*

Labelling: 3

IATA / ICAO

UN no: 1263
Packing group: II
Labelling: 3

Class: 3
Packing instructions: 305(P&CA); 307(CAO)

15. REGULATORY INFORMATION (CHIP)

Hazard symbols: Irritant.



Risk phrases: R36: Irritating to eyes.
R67: Vapours may cause drowsiness and dizziness.

Haz. ingredients (label): PROPAN-2-OL

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

15. REGULATORY INFORMATION (CLP)**16. OTHER INFORMATION**

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.
* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R11: Highly flammable.
R36: Irritating to eyes.
R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.