

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** PRO-SPRAY H20 BASECOAT SUPER YELLOW TINTER

**Product code:** VST-630

**INCI name:** 2084237

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** Pro-Spray Automotive Finishes Limited  
Unit H  
Normandy Lane, Stratton Business Park  
Biggleswade  
Bedfordshire  
SG18 8QB  
United Kingdom

**Tel:** +44 (0) 1767 314320

**Fax:** +44 (0) 1767 319044

**Email:** [colour@pro-spray.co.uk](mailto:colour@pro-spray.co.uk)

### 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1767 314320  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Eye Irrit. 2: H319; Skin Irrit. 2: H315

**Classification under CHIP:** This product has no classification under CHIP.

### 2.2. Label elements

**Label elements under CLP:**

**Hazard statements:** H315: Causes skin irritation.  
H319: Causes serious eye irritation.

**Signal words:** Warning

**Hazard pictograms:** GHS07: Exclamation mark



# SAFETY DATA SHEET

PRO-SPRAY H2O BASECOAT SUPER YELLOW TINTER

Page: 2

**Precautionary statements:** P264: Wash thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332+313: If skin irritation occurs: Get medical advice/attention.  
P337+313: If eye irritation persists: Get medical advice/attention.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### 2-BUTOXYETHANOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
203-905-0	111-76-2	Xn: R20/21/22; Xi: R36/38	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	6.225%

#### Non-hazardous ingredients:

##### WATER

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	7732-18-5	-	-	20.990%

##### COPOLYMER OF ACRYLIC ACID

-	-	-	-	15.200%
---	---	---	---	---------

##### C. I PIGMENT 184

237-898-0	-	-	-	3.600%
-----------	---	---	---	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.  
Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

PRO-SPRAY H2O BASECOAT SUPER YELLOW TINTER

Page: 3

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

[cont...]

# SAFETY DATA SHEET

PRO-SPRAY H2O BASECOAT SUPER YELLOW TINTER

Page: 4

## 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Do not handle in a confined space. Avoid the formation or spread of mists in the air.  
Smoking is forbidden.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed.  
**Suitable packaging:** Must only be kept in original packaging.

## 7.3. Specific end use(s)

**Specific end use(s):** FOR PROFESSIONAL USE ONLY

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**2-BUTOXYETHANOL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50 ppm	-	-

### 8.1. DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure all engineering measures mentioned in section 7 of SDS are in place.

**Respiratory protection:** Compressed airline breathing apparatus (EN139). Respiratory protective device with particle filter.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses with side-shields. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Odour:** Characteristic odour

**Solubility in water:** Miscible

**Flash point°C:** 66

**VOC g/l:** 268

[cont...]

# SAFETY DATA SHEET

PRO-SPRAY H2O BASECOAT SUPER YELLOW TINTER

Page: 5

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### 2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

**Toxicity values:** No data available.

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]

# SAFETY DATA SHEET

PRO-SPRAY H2O BASECOAT SUPER YELLOW TINTER

Page: 6

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

[cont...]

## SAFETY DATA SHEET

PRO-SPRAY H20 BASECOAT SUPER YELLOW TINTER

Page: 7

**Phrases used in s.2 and 3:** H302: Harmful if swallowed.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
R36/38: Irritating to eyes and skin.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.